



Declaration of Performance

REGULATION (EU) NO 305/2011

PRODUCT

IDENTIFICATION CODE	FugeMads Design Sealant
BATCH NO.	See imprint on packaging
INTENDED USE	One-component silicone sealant, neutral curing. Sealant for external and internal, non-structural use: facade joints, type F ext-int CC; glazing applications, type G ext-int CC; sanitary joints, type S; joints in pedestrian walkways, type PW ext-int CC.
MANUFACTURER	FugeMads ApS Kirkevej 46 DK-4872 Idestrup Denmark
SYSTEM OF AVCP	3 plus 3
NOTIFIED BODY	MPA Dortmund (NB No. 0432) performed initial type testing under system 3 and issued the test report.
HARMONISED STANDARD	EN 15651:2012 — Parts 1 (F), 2 (G), 3 (S) and 4 (PW)

ESSENTIAL CHARACTERISTICS

Declared performance

FIRE BEHAVIOUR	Class E
DANGEROUS SUBSTANCES	Assessed (see SDS)
RESISTANCE TO FLOW	$\leq 3 \text{ mm}$
VOLUME LOSS	$\leq 10 \%$
ELASTIC RECOVERY	$\geq 70 \%$
ADHESION/COHESION (DRY, WET, COLD, LIGHT)	No failure
RESISTANCE TO MICROORGANISMS	0 or 1
DURABILITY	No failure

DECLARATION

The performance of the product identified above is in conformity with the declared performance listed. This declaration of performance is issued under the sole responsibility of FugeMads ApS.

SIGNED FOR AND ON BEHALF OF THE MANUFACTURER



Mads Henriksen

Founder

Idestrup, August 30, 2026